Lockheed Martin Corporation
6801 Rockledge Drive ±MP CCT 246
Bethesda, Maryland 20817



6XEPLWWHG (OHFWURQLFDOO\ YLD H'(3

6HSWHP, 2018U

Subject: 68%0,77$/ 2) 83'$7(' *5281':$7(5 021,725,1* 3/$1
3RVW 7HPSRUDU\ 6OXWLRQ 2SHUDWLRQV 0DLQWHQDQFH
Former General Electric Facility, 50 Fordham Roa d, Wilmington, MA, RTN 3- 0518

Dear 0DVV'(3:

Lockheed Martin &RUSRUDWLRQ0D³URVELQXHEHPG WW\KDHWQWDXFSKGHDGWHG
JURXQGZDWHUWRQLWRULQJSODQIRU 7HPSRUDU\6OXWLRQDQG3HUPDQHQW5HPHGLDO
DQGGRQLWR2ULQJSODQW\HDUE\ UHIHUHQFHG

7KH3SUL7HPSRUDU\6OXWLRQ GHVFULEHVWKH3HUVW 7HPSRUDU\6OXWLRQ
SODQQRQFODXGHGHIDEXQGZDWHUSHUIRUPDQFHPRQLWRULQJSURJUDP
JURXQGZDWHUWRUHPHGLDWLRQV\VWHPV RSHUDWLRQDQGPDLQWHQDQFH
RYHUWLPHRYHUEXUGHQGURUFRXQGZDWHUWUHDWPHQWV\VWHPV DQGSLQDOHW
VWDEOHQHRBWQJDWLQJ

$VVWDWHGLQWKH7HPSRUDU\6OXWLRQ HPSKDVL]HG LPLQDU\ JURRQLQWHUHVW
7DEOH ZDVUHVHQWWRGDVSHSUR[LPDWHGLVWDQFH2UROXQGZDWHU
VDPSOLQJQDOXQGDOVVFRVS7HKJURXQGZDWHUPRQLWRULQJ
6HSWHPEHU 2FWREHXEXLKHUURXQGZDWHUQHWZRUNDGGLWLRQDO
DGGLWLRQDO3RLQWV

/RFNKHOHG&RUSRUDWLRQSRUKDWXEQK HU HWYKRHYXHDWEKGQGEHQGURFRXQGZDWHU
GDWRDWKVHLWKURR2XJKREHUQG KXSYGDWKDQQXDO JURXQGZDWHU
PRQLWRULQJRXWOLQHGQRXWOLQHGW7KEHGF7KL2V0 JURXQGZDWHU
LQFOXGHVLZDQGGDYHFURWLFDWRWKH R YHUEXEHGHUQRFXPEHRWKHU
DQGGGRZQJUDGLHQWZKHDHQYDOLWHW LQFKOXGHVWHWDEOHH\SUHRXQGZDWHU
YRODWLOHRPSRXQGV YRODW
SHWURKOHXPKLGURFDUERQV SHWURDQG GLVVROYHGHOHPHQWV
WKZDWHUEHX VHLQGRFXPHQWWLQJRWWHRGHWHUPLQH
JURXQGZDWHU

7KLVSGDZWHGJURXQGZDWRQLWRULQJSURJUDQEEHUIRUPHGQQLWKHB O O
PRQLWRUVHOHQW[SDQGHUQGZDWLWRULQJ\E H

Table 1
Post-Temporary Solution O and M Groundwater Sampling Scope
Former GE Site, Wilmington, MA

Area	Location ID	FLUTe port	Interval	Well Diameter (inch)	Screen Interval (Ft bgs)
Ô y vè ðlFü'Ì Á6½tÁO\@Ùm` Á÷w` ¡ Á 6O¿µW BE ¬»hî¨ú;Ì"R{ú{ 74ætxß$					

Table 1
Post-Temporary Solution O and M Groundwater Sampling Scope
Former GE Site, Wilmington, MA

Area	Location ID	FLUTe port	Interval	Well Diameter	(inch)	Screen Interval (Ft bgs)	VOCs (SW846 -USEPA Method 8260C)	1,4 dioxane (SW846/USEPA Method 8270D SIM) to get DL <0.3 ug/l)	Field Parameters: pH, temperature, conductivity, ORP, DO, and turbidity	CSIA: 13C/12C ratio for PCE, TCE, Cis 1,2 -DCE, VC (Pace Analytical)	Isotopic Analysis: O16/O18, H1/H2 and S34/S36	VPH (MassDEP VPH 04 1.1 Revision 1)	EPH and polycyclic aromatic hydrocarbons (PAH) (MassDEP EPH 04 1.1 Revision 1)	Total As, Fe, Mn (SW846 - U SEPA Method 6010C)	Dissolved As, Fe, Mn (field filtered) (SW846 - USEPA Method 6010C)	Chloride (USEPA 300.0)	Nitrite	Nitrate (USEPA 300.0)	Sulfate (USEPA 300.0)	Sulfide	Total organic carbon (SW 846 9060A)	Methane, Ethane, Ethene, Acetylene, Butane (Pace-Microseeps AM20Gax)P60S6K

Table 1
Post-Temporary Solution O and M Groundwater Sampling Scope
Former GE Site, Wilmington, MA

Area	Location ID	FLUTe port	Interval	Well Diameter	(inch)	Screen Interval (Ft bgs)	VOCs (SW846 -USEPA Method 8260C)	1,4 dioxane (SW846/USEPA Method 8270D SIM) to get DL <0.3 ug/l)	Field Parameters: pH, temperature, conductivity, ORP, DO, and turbidity	CSIA: 13C/12C ratio for PCE, TCE, Cis 1,2 -DCE, VC (Pace Analytical)	Isotopic Analysis: O16/O18, H1/H2 and S34/S36	VPH (MassDEP VPH 04 1.1 Revision 1)	EPH and polycyclic aromatic hydrocarbons (PAH) (MassDEP EPH 04 1.1 Revision 1)	Total As, Fe, Mn

VPH