			onsite survey and approval. The Manufacturer's Quality System will be subject to review and approval at all times by Lockheed Martin.
QQLS	1	PRODUCT ASSURANCE EXHIBIT "S" APPLIES	The applicable Product Assurance requirements are contained in Exhibit "S" to the Statement of Work previously provided to the Supplier.
QT4A	1	QMS—QUALITY SYSTEM REQUIREMENTS (SAE AS9120)	

QM8	Q	PRINTED WIRING BOARD FABRICATION REQUIREMENTS	Fabrication requirements per 3GPS-RQ-09-0080, for rigid boards, or 3GPS-RQ-09-0081, for flex and rigid flex boards, are invoked on this order. In the event of a conflict between 3GPS-RQ-09-0080 or 3GPS-RQ-09-

QTP	Q	PRODUCT ASSURANCE OD63425 APPLIES	Active Supplier and supplier's subtiers shall comply with the requirements of the current issue of OD63425 for all materials and processes specified in design disclosure called out in this purchase order or subcontract. Requests for changes to OD63425 to add or modify substitutions shall be submitted to LM subcontracts via a Supplier (Supplier) Request for Information or Change (VRIC) in accordance with A689426.
CERTIFICATE OF CONFORMANCE			
Q1L	Q	C of C for Group A, B, C, D, and/or E Tests	The supplier shall submit a Certificate of Conformance (C-of-C) indicating that Group A, B, C, D and/or E tests were performed, as required by the procurement document, per applicable Military specification(s).This C-of-C shall indicate the specific group(s), lot number(s), date code(s), and part number(s) that qualified the product.
QA5	Q	CERTIFICATE OF CONFORMANCE REQUIRED BY LM	Organization (Supplier, Dealer Distributor, or Manufacturer) shall provide a certification with each shipment to attest that the materials furnished to Lockheed Martin are in conformance with applicable requirements of the Contract. Certification must contain the following: -Lockheed Martin Purchase Order number -Part number specified on Lockheed Martin PO -Name and address of manufacturing location (or Cage Code) -Quantity shipped -Manufacturer's traceability is required (Ex. Lot, heat, batch, date code, serial number), except for commercial specification items that do not have a traceability requirement -Signature and date by company representative (electronic signature is acceptable) The applicable material test results, process certifications and inspection records shall be presented upon Customer's request. Organization shall perform inspection, as necessary, to determine the acceptability of all articles under this Order. All articles submitted by Organization under this Order are subject to final inspection and acceptance at Customer's plant.
QB11	Q	CERTIFICATE OF COMPLIANCE FOR LEAD CONTENT	Electronic, electrical, electro-mechanical and/or mechanical piece parts, and assemblies (including internal hardware) shall NOT have tin plating or tin finishes with <3% lead (Pb) content by weight. This requirement also applies 3Neat)a15( )102(a)25(e)27(s)-28(t)9(a)27(n)al

conform to requirements specified in the contract, drawings, specifications, or other approved product description. Includes failures, discrepancies, defects, anomalies, and malfunctions.

Rework: Used when an article can be made to conform to drawing requirements. Detailed instructions must be included or referenced.

Repair: Used when the nonconforming article, material or service can be corrected to a usable condition, although its condition will not be identical with drawing / specification requirements. "The organization shall ensure that product which does not conform to product requirements is identified and controlled to prevent its unintended use or delivery.

The controls and related responsibilities for dealing with nonconforming product shall be defined in a documented procedure.

The organization's documented procedure shall define the responsibility for review and authority for the disposition of nonconforming product and the process for approving personnel making these decisions."

Data Requirements: Any nonconformance discovered by the organization, on products in their control, shall be documented by the organizations' approved method of nonconformance reporting. This shall include a detailed description of the nonconformance; location (by drawing reference point, hardware reference point, clock location, etc.); and exact callout of the violation by drawing or specification requirement (including, sub-paragraph or illustration number). It shall also list what type of inspection revealed the discrepant condition, and what, if any, subsequent actions were taken prior to disclosure. Dimensional violations shall include "should be" and "is" dimensions, and tool(s) calibration traceability numbers.

Nonconformance Preliminary Review: The preliminary review process shall be initiated with the identification and documentation of a nonconformance. A preliminary review shall be the initial step performed by the organization to determine if the nonconformance needs to be reported to the customer (see below), and to determine if the nonconformance is minor and can be re-worked to a condition that completely conforms to the drawing or specification requirements.

Note: preliminary review does not negate the requirement to identify, segregate, document, report and disposition nonconformances.

QB4F			3. Turnaround, maintenance, overhaul, and repair of flight, ground test operation or shipping and receipt of hardware delivered to the customer including any test involving hardware previously accepted by the customer and returned for repair, modification, etc. · And it is: 1. Flight hardware 2. Flight Hardware Spares 3. Equipment that is representative of flight hardware (flight-like hardware), including prototype and qualification hardware 4. Ground Support Equipment (GSE) that is safety critical

QTB5	Q	NONCONFORMING ITEMS SEPARATION	Supplier shall identify and segregate nonconforming supplies in order to prevent their use, shipment or commingling with conforming supplies. Only Buyer's Material Review Board may authorize acceptance. Request disposition of nonconforming supplies on Supplier Request for Information or Change (VRIC).
QTM5	Q	REJECTED MATERIAL RESUBMISSION	Any items under this order which are rejected by Buyer and returned to Supplier for repair or replacement

			contact for the appropriate Procurement Quality Assurance Representative (PQAR) assignment. Source inspection shall be conducted by the Customer at the Organization's facility or where designated in the Order. The Organization shall notify PQAR office a minimum of five (5) working days in advance of the time the articles or materials are ready for inspection or test. The Organization shall make available to the PQAR all applicable drawings, specifications, procedures, statements of work, Customer's Order, test software, and changes thereto, related inspection and/or test equipment, and such other information as may be required to satisfactorily perform the inspections and tests required under this Order.
QAQC14A	Q		

			The First Article(s) shall be produced on production equipment and using processes which will be utilized on production runs. Additionally, the Organization shall perform additional First Article Inspection(s) per the requirements of AS9102 (i.e.: following every major tooling, every design change, and subsequent to any evident quality degradation for a specified part or article). Records of all first article activity will be documented as required in AS9102, treated as quality / acceptance records, and made available to Customer if requested.
QCF	Q	GOVERNMENT SOURCE INSPECTION C OF C	Hardware listed in this Purchase Order (PO) has Mandatory Government Source Inspection requirements, Classification of Characteristics (CC's). Supplier must contact local Defense Contract Management Agency (DCMA) Quality Assurance Representative, prior to start of production, to coordinate with DCMA the mandatory inspections. All CC inspection charac

D/C
S/N

			For information on how to use the ship-to-module, view the downloadable guide here. For suppliers approved to Q4M (SQDANQ4M00), refer to the Q4M definition located in the 253-01 document for specific ship-to-module directions.
QC2	Q	TIME AND TEMPERATURE SENSITIVE MATERIAL	

QPC	Q	UNRELEASED DOCUMENTATION CONTROL	When procurement is to LM unreleased documentation, supplier shall impound hardware upon completion

			RECORDS The contractor shall maintain fabrication records which summarize the identification of elements within an assembly. Records, shall include name of supplier, date of manufacture, screening date and other pertinent information.
QM17	Q	SINGLE DATE/LOT CODE	Parts delivered against this Contract shall be from a single date/lot code. The lot identifier shall be recorded on all certificates and packages for this order. Authorization for shipments with multiple date/lot codes must be pre-coordinateg0 GƤ7(o0 Gy.85 Tm0 u)27(n)27( )43(fL0 g0 (d)27( )43(p-15( )43( )-12(n)27(a)0 GM)43(s

QQZ304	1	SMP012701U05	SMP012701U05, Supplier Technical Program Management Requirements for Honeywell for the Manufacture of Small Reentry Body Inertial Measurement Unit (SRIMU)
QQZ9	1	SMP010710U05	SMP010710U05, Supplier Technical Program Management (STPM) for Support Equipment Suppliers - Updated
QZ187	1	D370408	D370408, LOA - Use of PA STD 8700-Q001A and PA STD 8700-Q002A
QZ238	1	D915700	LMSSC D915700, Supplier Technical Program Management (STPM) Document for Missile System Hardware (including Addendum 1 and Addendum 2) applies.
QZ253	1	D915710A	LMSSC D915710, Supplier Technical Program Management (STPM) Document for Missile System Division Support Equipment (including Addendum 1 and Addendum 2) applies.
QZ260	1	D915721	D915721, PA Quality Requirements for PCM Telemetry Systems
QZ263	1	D915740	LMSSC D915740, Supplier Technical Program Management (STPM) Document for Suppliers of Missile System Division (MSD) Hardware (including Addendum 1) applies.
QZ271	1	D915750	LMSSC D915750, Supplier Technical Program Management (STPM) Document for Missile Test and Readiness (including Addendum 1) applies.

QZ161	Q	A268140	A268140, PAWS 30 - Variables Test Data (VTD)
QZ162	Q	A268186	A268186, Special PAWS - Product Assurance Work Statement - Product Quality Provisions for Suppliers of Ordnance Devices
QZ163	Q	A268191	A268191, Special PAWS - Product Quality Provisions - Suppliers of Batteries
QZ164	Q	A268198	A268198, Special PAWS - Supplemental PA Rqmts for Suppliers of MSD Hardware
QZ165	Q	D054159	D054159, Special Tooling Requirements
QZ166	Q	D057311	D057311, LOA - Sundstrand Data/LMSC - PA Rqmts for C4 Interlocks Accelerometer PN 3063028
QZ167	Q	D062101	D062101, Surface Equipment Welding Procedure Certification and Welder Performance Qualification, Revision C

QZ204	Q	D824156	LMSSC D824156, Requirements for EEE Devices 8436 (including Addendum 1) applies.
QZ206	Q	D824157	D824157, PA ID 5>D 7>> BDC q135.1 523.13 22.225 10.007(,)5(o)27(r)-19( )43(E)20(E)20(E)20( )-15(D)16

QZ241	Q	D915701	D915701, PA Quality Rqmts for Electronic Components/Subassemblies.
QZ244	Q	D915702	D915702, PA Quality Requirements for Major Commodities
QZ246	Q	D915703C	D915703C, PA Quality Requirements for Trident II (D5) Connectors
QZ248	Q	D915703-1C	D915703-1C, PA Quality Requirements for G & H PMM Connectors
QZ249	Q	D915704	D915704, PA Quality Rqmts for Nose Cap & Nose Fairing Manufacture
QZ25	Q	F120014	F120014, LOA Btwn LMSC & Teledyne Wah-Chang Albany Pertaining to Procurement Rqmts for D5 PBCS Manifold
QZ250	Q	D915705	D915705, PA Quality Requirements for Trident II Batteries
QZ251	Q	D915706C	D915706C, PA Quality Rqmts for Printed Circuit Boards, Multilayer Boards, Rigid Flex Master Interconnect Board & Flex Cables
QZ252	Q	D915709P	D915709P, PAQR - Black Box Su

	Updated: QZ92	Per FBM Request
6/14/2007	Edited: QCF	Edit to wording per FBM Request
6/28/2007	Edited: QCF	Returned to original wording
8/20/2007	Update: QTP	Removed reference to Addendum 1 and 2
10/31/2007	Added: QTD2	Per FBM Request
1/31/2008	Added: QZ317	SMP010708U07 – FBM program specific
2/21/2008	Added: QT12	Seller Rating Test Documentation Twelve Years - per Special Programs Request
	Edited: Q0W	Changed the word "record" to "mark/identify" - per Central Procurement Request
7/28/2008	Added: QZ318	SMP010713U08 – FBM program specific
	Added: QA5	Certification of Conformance Required By LMSSC
9/24/2008	Added: QTC6	Counterfeit Part Avoidance
12/15/2008	Added: QWGC	Work Group Collaboration (Online data submittal)
2/13/2009	Added QZ319	

11/17/2015	Removed: Q19B, Q37, Q57, QA2C, QA4H, QAQC05, QAQC07, QAQC10, QAQC12, QAQC18, QAQC19, QAQC30, QAQC31, QB12, QCC, QD13, QD15, QD16, QD5, QD8, QGL, QLT, QP3, QQD4K7, QQMY, QQS5, QQS5C, QQT8, QQTC5, QS11, QS5B, QS7, QT4C, QT4F, QTB9, QTC1, QTC3, QTR	Codes Deactivated
	Edited: QAQC13	Updated text to align with the language required by the Acquisition Compliance matrix
9/26/2016	Removed: QTU	